

TECHNICAL DATA SHEET

| | HC-H305# |
|--------------------|---|
| PROPERTIES | Semi / fully automatic packing machine, Carton packing, Food box, Sucker adhesion, etc. |
| DESCRIPTION | High viscosity、Non wire drawing、Cold-resistance、No loss of viscosity、Non-toxic, etc. |
| | Basis:EVA &Tackifier resin,paraffin,antioxidant. Composition:Non-hazardous according to Directive Color: white Appearance:flake |
| TECHNICAL DATA | Viscosity (180°):1600 ± 3000 CPS Softening time:75℃ ±5℃ Open time:10~15S Set time:2~3S Application temp.: 150℃-180℃ |
| Application Method | Roller, coating, spraying |
| PACKAGING | 1KG/BAG(BOX)、25KG/CTN, ETC. |
| INFORMATION | CAS NO:24937-78-8 69430-35-9 9002-88-4 6683-19-8 HS CODE:3506.91.9090 shipping: suitable. Certification:SGS、ROHS、MSDS |
| REMARK | This information provided is based on our knowledge and experience and only for user reference. At the same time, due to the use of different materials and changes in working conditions being beyond our control range, we solemnly suggest that the users can conduct an exhaustive experiment to use parameters in the end. |

SUZHOU OUSHIDA HOT MELT GLUE MACHINERY EQUIPEMNTCO.,LTD TEL:+86-512-65564669FAX:+86-512-65488511NO.12 HUCUNDANG RD CAOHU INDUSTRIAL ZONE XIANGCHENG DIST SUZHOUContact: FREDEmail: FRED@SZOSD.CN