



TECHNICAL DATA SHEET

| | |
|---------------------------|---|
| | HC-H323# |
| PROPERTIES | Widely use 、 Electronic、 Handcraft 、 Toy、 Carton packing、 Metal、 Plastic、 Box |
| DESCRIPTION | High viscosity、 Non wire drawing、 Cold-resistance、 No loss of viscosity、 Non-toxic, etc. |
| | <p>Basis:EVA &Tackifier resin,paraffin,antioxidant. Composition:Non-hazardous according to Directive Color: transparent Appearance:granule</p> |
| TECHNICAL DATA | <p>Viscosity (180°):6500±200 CPS Softening time:82℃±5℃ Open time:10~15S Set time:15~25S Application temp.: 120℃-160℃</p> |
| Application Method | Roller, coating, spraying |
| PACKAGING | 1KG/BAG(BOX)、 25KG/CTN, ETC. |
| INFORMATION | <p>CAS NO:24937-78-8 69430-35-9 9002-88-4 6683-19-8 HS CODE:3506.91.9090 shipping: suitable. Certification:SGS、 ROHS、 MSDS</p> |
| REMARK | This information provided is based on our knowledge and experience and only for user reference. At the same time, due to the use of different materials and changes in working conditions being beyond our control range, we solemnly suggest that the users can conduct an exhaustive experiment to use parameters in the end. |

Suzhou Oushida Hot Melt Machinery Equipment Co.,Ltd.

TEL:+86-512-65564669 FAX:+86-512-65488511

NO.12 HUNCUNDANG RD CAOHU INDUSTRIAL XIANGCHENG GUANGZHOU

Contact: FRED Email: FRED@SZOSD.CN