

SUZHOU OUSHIDA HOT MELT MACHINERY EQUIPMENT CO., LTD

TECHNICAL DATA SHEET

PRODUCT	HC-H3013#
USE	Food box, Carton packing, Box packing, Type A corrugated paper, Optical film and other paper adhered (suitable for semi-automatic / full-automatic packaging machine)
PROPERTIES	High viscosity、 Non wire drawing、 Cold-resistance、 No loss of viscosity、 Non-toxic, etc.
DESCRIPTION	Basis: EVA &Tackifier resin,paraffin,antioxidant. Composition: Non-hazardous according to Directive Color: Light Yellow Appearance: round
TECHNICAL DATA	Viscosity (180°): 3500 ± 3000 CPS Softening time: 90℃ ± 5℃ Open time: 5~7S Set time: 2~3S Application temp.: 150℃-180℃
Application Method	Roller, coating, spraying
PACKAGING	1KG/BAG(BOX)、 25KG/CTN, ETC.
INFORMATION	CAS NO: 24937-78-8 69430-35-9 9002-88-4 6683-19-8 HS CODE: 3506.91.9090 shipping: suitable. Certification: SGS、 ROHS、 MSDS
REMARK	This information provided is based on our knowledge and experience and only for user reference. At the same time, due to the use of different materials and changes in working conditions being beyond our control range, we solemnly suggest that the users can conduct an exhaustive experiment to use parameters in the end.

SUZHOU OUSHIDA HOT MELT MACHINERY EQUIPMENT CO., LTD

Caohu Industrial Park, Xiangcheng District, Suzhou

Contact: Fred

Email: fred@szosd.cn

31.Dec.2018